

# HME DX200™ vs. Telex BTR300 & BTR600

<b>Feature</b>	<b>DX200</b>	<b>BTR300</b>	<b>BTR600</b>
<b>RF Frequency Range</b>	<b>2.4-2.4835 GHz FHSS</b>	<b>150-216 MHz Crystal-Controlled</b>	<b>520-760 MHz Crystal-Controlled</b>
<b>Base Transmit Power</b>	<b>100 mW</b>	<b>50 mW</b>	<b>25 mW Typical</b>
<b>License-Free Operation</b>	<b>YES</b>	<b>NO</b>	<b>NO</b>
<b>Antenna and Channel Diversity</b>	<b>YES</b>	<b>NO</b>	<b>NO</b>
<b>Automatic Frequency Selection</b>	<b>YES</b>	<b>NO</b>	<b>NO</b>
<b>Wireless Isolated Channel</b>	<b>YES</b>	<b>NO</b>	<b>NO</b>
<b>Simultaneous 2-Wire and 4-Wire Operation</b>	<b>YES</b>	<b>NO</b>	<b>YES</b>
<b>RTS® and ClearCom® 2-Wire Interface Support</b>	<b>YES</b>	<b>YES</b>	<b>RTS® Only (Standard)</b>
<b>Remotely "Unlatch" Beltpacs from Transmitting</b>	<b>YES</b>	<b>NO</b>	<b>NO</b>
<b>Beltpac Transmit Power</b>	<b>100 mW</b>	<b>50 mW</b>	<b>25 mW</b>
<b>Voice Prompts</b>	<b>YES</b>	<b>NO</b>	<b>NO</b>
<b>ISO+ Mode</b>	<b>YES</b>	<b>NO</b>	<b>NO</b>
<b>Internal Beltpac Antennas</b>	<b>YES</b>	<b>NO</b>	<b>NO</b>
<b>Low Battery Indication</b>	<b>LED Blink &amp; Voice Prompt</b>	<b>LED Only</b>	<b>LED Only</b>
<b>Beltpac Weight</b>	<b>7.4 oz.</b>	<b>13 oz.</b>	<b>22 oz.</b>